

Oxygen meter inoLab[®] Oxi 7310 Set 1

Scope of supply: Device, oxygen sensor CellOx[®] 325, electrolyte, abrasive foil, replacement membrane caps, universal power supply, stand, operating instructions, CD-ROM with software, USB cable

Concentration resolution:	0.01/0.1
Concentration accuracy:	± 0.5 % of measured value
Saturation:	0 ... 600 %
Saturation resolution:	0.1/1
Saturation accuracy:	± 0.5 % of measured value
Partial pressure:	0 ... 1250 hPa
Partial pressure resolution:	0.1/1
Partial pressure accuracy:	± 0.5 % of measured value
Temperature:	-5 ... 105 °C
Accuracy temperature:	± 0.1 °C
Dimensions (WxDxH):	190 x 230 x 80 mm
Power supply:	100 ... 240 V, 50/60 Hz
Battery/rechargeable battery:	4 x 1.5 V, AA
IP code:	IP 43

Type	Concentration	Min. temperature °C	Max. temperature °C	Width mm	Depth mm	Height mm
inoLab [®] Oxi 7310 Set 1	0 ... 90 mg/l	-5	105	190	230	80

Zubehör:

Oxygen sensor StirrOx[®] G / Xylem Analytics Germany (WTW)
Oxygen sensor DurOx[®] 325 / Xylem Analytics Germany (WTW)
Cleaning solution for galvanic oxygen sensors / Xylem Analytics Germany (WTW)

Alternativen:

Oxygen meter inoLab[®] Oxi 7310 / Xylem Analytics Germany (WTW)