

# Precision balances Explorer Plus EXP

The Explorer EXP series offers hassle-free data transfer with driverless HID (Human Interface Device). The time synchronization NTP function confirms data traceability to meet pharmaceutical regulations.

- 7 inch touchscreen
- Detachable terminal
- Motorised leveling system with digital leveling bubble
- Touchless sensors
- Full metal housing
- Internal calibration systems
- 2 x USB-A, 1 x USB-B, 1 x USB-C, Ethernet, 1 x RJ11, 1 x RS232
- Optional: Bluetooth<sup>®</sup>/WiFi

Weighing plate (WxD): 178 x 201 mm  
 With draft shield: No  
 Dimensions (WxDxH): 229 x 408 x 97 mm  
 Weight: 5.5 kg  
 Power supply: 100 ... 240 V·AC, 50/60 Hz

Type	Max. load g	Readability g	Reproducibility g	Linearity	Verified calibration	Type of display	Width mm	Depth mm
EXP2202	2200	0,01	0,007	&plusmn;0,006 g		TFT	229	408
EXP2202M	2200	0,01	0,007	&plusmn;0,006 g	Verified	TFT	229	408
EXP4202	4200	0,01	0,007	&plusmn;0,006 g		TFT	229	408
EXP4202M	4200	0,01	0,007	&plusmn;0,006 g	Verified	TFT	229	408
EXP6202	6200	0,01	0,007	&plusmn;0,006 g		TFT	229	408
EXP6202M	6200	0,01	0,007	&plusmn;0,006 g	Verified	TFT	229	408
EXP8202	8200	0,01	0,007	&plusmn;0,006 g		TFT	229	408
EXP8202M	8200	0,01	0,007	&plusmn;0,006 g	Verified	TFT	229	408
EXP12202	12200	0,01	0,007	&plusmn;0,006 g		TFT	229	408
EXP12202M	12200	0,01	0,007	&plusmn;0,006 g	Verified	TFT	229	408
EXP6201	6200	0,1	0,07	&plusmn;0,06 g		TFT	229	408
EXP6201M	6200	0,1	0,07	&plusmn;0,06 g	Verified	TFT	229	408
EXP8201	8200	0,1	0,07	&plusmn;0,06 g		TFT	229	408
EXP8201M	8200	0,1	0,07	&plusmn;0,06 g	Verified	TFT	229	408
EXP10201	10200	0,1	0,07	&plusmn;0,06 g		TFT	229	408
EXP10201M	10200	0,1	0,07	&plusmn;0,06 g	Verified	TFT	229	408

- Alternativen:  
 Precision balances High Capacity Explorer Plus EXP / Ohaus  
 Precision balances Explorer EXR, with draftshield / Ohaus  
 Precision balances Explorer EXR / Ohaus